

# Patent Abstracts of Japan

PUBLICATION NUMBER : 09186337  
PUBLICATION DATE : 15-07-97


APPLICATION DATE : 08-01-96  
APPLICATION NUMBER : 08000397

APPLICANT : ADVANCED DISPLAY:KK;

INVENTOR : NAKAHORI MASAKI;

INT.CL. : H01L 29/786 H01L 21/336 G02F 1/136

TITLE : METHOD OF MANUFACTURING THIN  
FILM TRANSISTOR AND  
ELECTRO-OPTIC DISPLAY UNIT  
FORMED BY THIS METHOD



ABSTRACT : PROBLEM TO BE SOLVED: To avoid the contamination by impurities such as phosphorus etc., while reducing the load of a plasma CVD device at low operation rate and high cost to increase the processing capacity for cutting down the manufacturing cost.

SOLUTION: A gate electrode 2 is pattern-formed on a glass substrate 1 so as to continuously form a gate insulating film 3 and an undoped amorphous silicon 4 by CVD process on the gate electrode 2. Next, an n type amorphous silicon 5 is formed on the whole substrate surface near the surface of this undoped amorphous silicon 4 by ion implanting process in an ion implanting device. At this time, the accelerating voltage is set up to be at 10keV So that the lower part of the undoped amorphous silicon 4 may not be affected by the ion implantation. Besides, the impurity concentration of the n type amorphous silicon 5 is specified not to exceed  $1 \times 10^{18}$  (atoms/cm<sup>3</sup>) in the region exceeding 50nm distant in the depth direction from the surface.

COPYRIGHT: (C)1997,JPO

BEST AVAILABLE COPY